

# IDM-17VHT

17 Industrial multi-touch monitor with HDMI&VGA



## Features

- 17" SXGA TFT LCD Panel support 1280x1024 pixels,450 cd/m2 brightness
- 6mm rugged aluminum bezel panel and Rugged construction
- Input signal : VGA + HDMI + AUDIO
- Built-in 2 x stereo speakers for automation system voice output
- OSD control keys on the side of rear panel
- AC 100-240V wide range external ac adapter
- 8 ~ 30V DC input power module(Optional)
- Panel ( Flush ) mount with bracket and with standard VESA hole ( 100x100 mm )
- Application for HMI, Kiosk, Automation, M2M, IOT system,Robots, shopping mall, Restaurant etc.

## Specifications

LCD Panel	
Display Type	17" SXGA TFT LCD(Backlight LED)
Resolution	1024x768
Max.color	16.7M
Luminance	450 cd/m2
View Angle	140°(H) , 110°(V)
Pixel Pitch	0.264 x 0.264 mm
Contrast Ratio	1000:1
Response Time	5 ms
LED MTBF	50,000hrs
System	
Touch screen	Capacitive (10-points multi touch)
Input Signals	VGA+HDMI+Audio
DC-DC input(optional)	8 ~ 30V DC input power module

Power Supply	Input 100~240VAC,50/60Hz external ac adapter (Output DC12V@ 5A / 60W)
Mechanical and Environmental	
Operating Temperature	0 °C to 60 °C
Storage Humidity	5% to 95%@ 40°C , on-condensing
Vibration	5-17Hz/1mm amplitude, 17-640Hz/1.5g acceleration
Shock	10G peak acceleration (11 msec. duration)
Dimensions (WxHxD)	408 x 345 x 47 mm
Weight	Net: 8.3kg , Gross:10.9kg

## Ordering Informations

IDM-17VHT	17" LCD Industrial Multi-touchMonitor with VGA + HDMI + Audio input, with 2 x stereo speakers
-----------	---

## Dimensions Diagram

