



Features

- 10.4" TFT LCD Panel support 800x600 pixels
- Material: Aluminum magnesium Alloy
- Rugged construction design
- Input signal : VGA/AV
- 350 cd/m2 brightness
- Resistive type of touchscreen
- NEMA4/IP65 compliant front panel
- Panel mounting with clip
- Meet standard VESA hole , support desktop stand / wall mount / swing arm mounting

Specifications

Display	
Size	10.4" TFT LCD
Resolution	800x600
Color	262K
Backlight	2xCCFL
Luminance	350 cd/m2
Contrast Ratio	250:1
View Angle	120°(H) , 110°(V)
LCD MTBF	50,000hrs
System	
Construction	Aluminum magnesium Alloy
Color	Black
I/O	DC input/VGA/AV/USB(COM optional)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall
Installation	Install on desk,Hanging on the wall or VESA cantilever install
Power Supply	DC 12V input
Touchscreen(Optional)	
Type	Resistive Touchscreen
Resolution	4096*4096
Controller Interface	Internal USB (RS-232 interface option)
Light Transmission	81% or more
Operating Force	≤250g
Life Expectancy	10 Millions
Environmental	
Operating Temperature	0 °C to 60 °C
Storage Humidity	5% to 95%@ 40°C, on-condensing
Vibration	5-17Hz/1mm amplitude, 17-640Hz/1.5g acceleration
Shock	10G peak acceleration (11 msec. duration)
IP Leve (Front Panel)	IP65
Safty	FCC/VDE(Level A)
MBTF	>50,000hrs

Packing info	
Dimensions	294x234x45 mm
Packing Dimension	406x340x140mm
NET weight	3KG
Packing list	12v @10A Power adapter x1, User manual x1,Warranty card x1, Packing list x1, Driver CD x1, Screws x1 bag, Touch pen x1, Clipx4

Ordering Informations

IEC-610	IEC-610 Chassis, 10.4" TFT LCD, 10.4" touchscreen, VGA
---------	--

Dimensions Diagram

