



### Features

- 19" TFT LCD Panel support 1280x1024 pixels
- Material: Aluminum magnesium Alloy
- Rugged construction design
- Input signal : VGA/AV
- 250 cd/m2 brightness
- Resistive type of touchscreen
- NEMA4/IP65 compliant front panel
- Panel mounting with clip
- Meet standard VESA hole , support desktop stand / wall mount / swing arm mounting

### Specifications

Display	
Size	19" TFT LCD
Resolution	1280x1024
Color	16M
Backlight	2xCCFL
Luminance	250 cd/m2
Contrast Ratio	700:1
View Angle	160°(H) , 140°(V)
LCD MTBF	50,000hrs
System	
Construction	Aluminum magnesium Alloy
Color	Black
I/O	DC input/VGA/AV/USB(COM optional)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall
Installation	Install on desk, Hanging on the wall or VESA cantilever install
Power Supply	DC 12V input
Touchscreen(Optional)	
Type	Resistive Touchscreen
Resolution	4096*4096
Controller Interface	Internal USB ( RS-232 interface option)
Light Transmission	81% or more
Operating Force	≤250g
Life Expectancy	10 Millions
Environmental	
Operating Temperature	0 °C to 60 °C
Storage Humidity	5% to 95%@ 40°C, on-condensing
Vibration	5-17Hz/1mm amplitude, 17-640Hz/1.5g acceleration
Shock	10G peak acceleration (11 msec. duration)
IP Leve (Front Panel)	IP65
Safty	FCC/VDE(Level A)
MBTF	>50,000hrs

Packing info	
Dimensions	470x385x55 mm
Packing Dimension	530x440x150 mm
NET weight	7KG
Packing list	12v @10A Power adapter x1, User manual x1, Warranty card x1, Packing list x1, Driver CD x1, Screws x1 bag, Touch pen x1, Clipx4

### Ordering Informations

IEC-619	IEC-619 Chassis, 19" TFT LCD, 19" touchscreen, VGA
---------	--

### Dimensions Diagram

